

Mail Server Configuration

Overview

Artifactory supports sending mail to notify administrators and other users for significant events that happen in your system.

Some examples are:

- Watch notifications
- Alerts for backup warnings and errors
- License violation notifications

To enable mail notifications, you need to configure Artifactory with your mail server details as described below.

Page Contents

- [Overview](#)
- [Setup](#)

Setup

To access the mail server configuration, in the **Admin** module select **Configuration | Mail**.

Setup is straightforward and can be verified by sending a test message. Simply click "Send Test Mail" in the **Configure Mail** screen.

The screenshot shows the 'Mail Configuration' page in the JFrog Artifactory Admin interface. The page title is 'Mail Configuration'. Under the 'Mail Server Settings' section, there is an 'Enable' checkbox. Below it are input fields for 'Host *', 'Port *' (with '25' entered), 'Username', 'Password', 'From' (with a help icon), and 'Subject Prefix' (with a help icon and '[Artifactory]' entered). There is also an 'Artifactory URL' field with a help icon and 'http://localhost:8082/artifactory' entered. Below these are two checkboxes: 'Use TLS' and 'Use SSL'. At the bottom of the settings area, there is an email address field with 'email@example.com' and a 'Send Test Mail' button. At the bottom right of the configuration area, there are 'Reset' and 'Save' buttons.

Enabled	When set, mail notifications are enabled
Host	The host name of the mail server
Port	The port of the mail server
Username	The username for authentication with the mail server
Password	The password for authentication with the mail server
From (optional)	The "from" address header to use in all outgoing mails.
Subject Prefix	A prefix to use for the subject of all outgoing mails
Artifactory URL (optional)	The Artifactory URL to use in all outgoing mails to denote links to Artifactory.

Use TLS	When set, uses Transport Layer Security when connecting to the mail server
Use SSL	When set, uses a secure connection to the mail server
Test Message Recipient	The email address of a recipient to receive a test message