

Properties

Overview

Artifactory allows you to place properties on both artifacts and folders. Setting (and deleting) properties is supported by local repositories or local-cache repositories. While you cannot set or delete properties on virtual repositories, you can retrieve them.

You can assign properties from the **UI**, via **REST** (see below), or **on deployment**, using [Matrix Parameters](#). Properties can also be used to [Control Artifacts Resolution](#).

Properties are **searchable** and can be combined with [Smart Searches](#) to search for items based on their properties and then manipulate all the items in the search result in one go.

Property Sets

You can define the collections of properties called 'Property Sets' in the user interface. In each property-set you can define properties and for each property specify whether the property is open, single-value or multi-value.

This impacts the user interface you see when setting a property value and when searching for property values. Using searchable properties in artifact management is a very powerful feature.

Page Contents

- [Overview](#)
 - [Property Sets](#)
- [Attaching Properties via the UI](#)
- [Attaching and Reading Properties via REST API](#)

Read More

- [Using Properties in Deployment and Resolution](#)



Properties are for Guiding, not for Restricting

When you define a property-set with 'strongly-typed' property values, those values are used to provide an intuitive, guiding UI for tagging and locating items.

The actual value does not force a strong relationship to the original property-set's predefined values. This is by design, to not slow-down common repository operations and for keeping artifacts management simple by allowing properties to change and evolve freely over time, without worrying about breaking older property rules.

Properties are therefore a helpful and non-restrictive feature.

Attaching Properties via the UI

When selecting any item in the tree browser, you can view its **Properties** tab to view or edit the properties attached to the item.

antlr-2.7.7.jar Download Actions

General Effective Permissions **Properties** Watchers Builds Governance

Add: **Property** | Property Set

Name * Value Add

Recursive ?

3 Properties

Filter by Property Delete Page 1 of 1

Property	Value(s)
build.name	genericDeploy
build.timestamp	1435677419561
build.number	30

To add a property, simply enter its name and value and click "Add".

To add multi-value properties, enter the values separated with a semi-colon (;). For example:

General Effective Permissions **Properties** Watchers Builds Governance

Add: **Property** | Property Set

Multivalue v1;v2;v3 Add

You can edit the value of any property by clicking on it

Edit 'Multivalue' Property X

v1;v2;v3

Cancel Save

Remote

Properties

Property	Value(s)
build.name	genericDeploy
build.timestamp	1435677419561
build.number	30
Multivalue	v1 v2 v3

Attaching and Reading Properties via REST API

Properties are a special form of metadata and are stored on items just like any metadata - in XML form.

In fact, you can view properties not only from the *Artifacts:Properties* tab, but also from the *Artifacts:Metadata* tab, in which you can examine properties as they are stored in XML form. The properties XML is using the `properties` root tag and has a very simple format.

You can set, retrieve and remove properties from repository items via REST API, as you would do with any other XML-based metadata.